



## PRICE LIST

Ref No. RRKL/LP/BCISI/03/21  
w.e.f. 1st March 2021

## SUPEREX FR

### FR PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
0.75	24/0.2	1039	24
1.0	14/0.3	1409	20
1.5	22/0.3	2062	12
2.5	36/0.3	3292	12
4.0	56/0.3	4800	8
6.0	84/0.3	7150	4
10.0	140/0.3	13115	3
16.0	126/0.4	21064	2

## UNILAY HR FR

### HR FR PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand Flexible High Conductivity plain annealed Copper, HR FR PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	37/0.19	1486	20
1.5	37/0.23	2164	12
2.5	61/0.23	3466	12
4.0	61/0.29	5288	8
6.0	91/0.29	7862	8

## FLAMEX FR-LSH

### FR-LSH PVC Insulated Single Core Cables



RR Kabel make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR-LSH PVC Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 694 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.0	14/0.3	1471	20
1.5	22/0.3	2165	12
2.5	36/0.3	3451	12
4.0	56/0.3	5039	8
6.0	84/0.3	7482	4

## FIREX LSOH HALOGEN FREE FLAME RETARDANT 90 °C, CROSSLINKED



RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, Cross linked Halogen Free Flame Retardant(HFFR) 90 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts, as per IS 17048 (HSN Code: 8544)

Size (Sq.mm)	Configuration	Rate/90 mtr	No. of Coils packed in an Outer Box
1.00	14/0.3	1763	20
1.50	22/0.3	2517	12
2.50	36/0.3	3977	12
4.00	56/0.3	5951	8
6.00	84/0.3	8620	4

\*FIREX LSOH – Insulation conforming to HFI XL 90 as per IS 17048

## RR KABEL FR / FR-LSH / LSOH



RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC / FR-LSH PVC / Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code: 8544)

RATE / 200 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulation As Per IS 17048
0.75	24/0.2	8	2340	2421	2738
1.0	32/0.2	13	3099	3208	3502
1.5	30/0.25	17	4545	4705	4999
2.5	50/0.25	24	7405	7664	8069
4.0	56/0.3	30	11189	11580	12219
6.0	84/0.3	38	16635	17177	18123

\*RR KABEL LSOH – Insulation conforming to HFI TP 70 as per IS 17048



## INDUSTRIAL CABLES

**RR** KÄBEL  
**WIRES & CABLES**

- FLEXIBLE SINGLE CORE CABLE
- FLEXIBLE MULTICORE CABLES
- SHIELDED CABLE
- BRAIDED CABLE

## RR KABEL FR / FR-LSH / LSOH




RR KABEL make single core unsheathed Multistrand High Conductivity plain annealed Copper, FR PVC / FR-LSH PVC / Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulated Industrial Cables in voltage grade upto and including 1100 Volts (HSN Code: 8544)

RATE / 100 MTR					
Size (Sq.mm)	Configuration	AMPS	RR KABEL FR FR PVC INSULATION As Per IS 694	RR KABEL FR-LSH FR-LSH PVC INSULATION As Per IS 694	RR KABEL LSOH Thermoplastic Halogen Free Flame Retardant (HFFR) 70 °C Insulation As Per IS 17048
10.0	140/0.3	52	14574	15084	16011
16.0	126/0.4	70	23180	23987	25337
25.0	196/0.4	88	37214	38703	41680
35.0	276/0.4	112	52055	54138	58302
50.0	396/0.4	146	73529	76470	82352
70.0	360/0.5	216	105205	109413	117830
95.0	480/0.5	262	140869	146503	157773
120.0	608/0.5	310	182272	189564	204146
150.0	750/0.5	355	225950	234988	253064
185.0	931/0.5	415	277466	288564	310762
240.0	1200/0.5	500	361520	375980	404902
300.0	1500/0.5	550	451323	469376	505482
400.0 *	2013/0.5	590	625311	650324	700348
500.0 *	2562/0.5	660	794963	826762	890358
630.0 *	3416/0.5	725	1056739	1099008	1183548

The item marked \* are non stock items refer to marketing dept for delivery schedule MOQ packing etc.

\*RR KABEL LSOH – Insulation conforming to HFI TP 70 as per IS 17048

## RATNA FLEX SINGLE CORE



Multistrand bright electrolytic annealed bare copper conductor, PVC Insulated Unsheathed Single core round flexible Industrial Power Cables for working voltages upto and including 1100 Volts (HSN CODE : 8544)

Size (Sq.mm)	Configuration	AMPS	Rate Per 100 Mtr
0.5	16/0.2	5	830
0.75	24/0.2	8	1196
1.0	32/0.2	13	1543
1.5	30/0.25	17	2231
2.5	50/0.25	24	3606
4.0	56/0.3	30	5658
6.0	84/0.3	38	8382