

POLYCAB

IDEAS. CONNECTED.

POLYCAB INDIA LIMITED**PCC LP No. 03/2025-26 Dtd : 18th December 2025-Revised****List of Products Covered in Our PCC LP****Aluminium Armoured / Unarmoured Cables****Copper Armoured / Unarmoured Cables****HT Cables****1.9 KV / 3.3 KV Cables for Solar****Instrumentation Cables****Rubber Cables****JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables****RS 485 Cables****Fire Survival Cables****FS Aluminium Cables**

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		213	238		265
4		242	260		303
6		294	321		384
10		372	415		527
16	239	423	446		564
25	315	452	594	690	738
35	382	564	755	838	956
50	470	730	982	1136	1277
70	601	978	1346	1531	1735
95	721	1207	1658	1920	2163
120	844	1455	2100	2428	2743
150	1006	1789	2578	2877	3373
185	1236	2150	3191	3642	4149
240	1527	2851	4075	4575	5357
300	1880	3494	5036	5628	6603
400	2374	4538	6437	7189	8243
500	2958	6127	8629	10162	11395
630	3649	7537	10969	12452	14958
800	4486				
1000	5517				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Armoured			
	Power (Al.)			
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
	Power Single Core (Al.)			
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		136	170		204
6		190	225		274
10		274	307		360
16	133	279	345		458
25	192	360	506	642	675
35	249	472	670	726	805
50	318	593	825	983	1076
70	439	853	1189	1343	1545
95	565	1012	1446	1717	1842
120	711	1274	1962	2229	2372
150	879	1583	2309	2607	2936
185	1088	1888	2910	3336	3635
240	1381	2470	3756	4082	4749
300	1706	3019	4604	5291	5783
400	2197	3766	5745	6610	7392
500	2760	4805	8130	9121	10310
630	3420	6116	10200	12101	13797
800	4268				
1000	5381				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	12%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		557	746	956	1402	1766	1946
6		784	1077	1407	2039	2491	2858
10		1247	1752	2287	3101		
16	1041	1807	2505	3308	4348		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	284	401	14	1315	2067
3	361	518	16	1470	2348
4	446	668	19	1744	2764
5	542	820	24	2181	3461
6	645	965	27	2426	3881
7	710	1089	30	2706	4668
8	908	1329	37	3510	5453
10	1034	1530	44	4100	6368
12	1149	1778	61	6035	9232

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
2 to 4 Core	7.5%	9%	22.5%	22.5%
5 to 10 Core	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		475	676	836
6		693	998	1229
10		1202	1692	2016
16	870	1656	2404	3086

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	222	335	14	1089	1968
3	313	468	16	1304	2255
4	401	631	19	1560	2667
5	489	790	24	1977	3367
6	588	937	27	2183	3740
7	666	1068	30	2591	4434
8	811	1211	37	3356	5317
10	968	1387	44	3925	6338
12	1034	1698	61	5743	8723

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D OXYGEN INDEX (FR)	4%
E) HR PVC Insulation	17.5%
HR PVC I/S & O/S	7.5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
G) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Unarmd			
2 - 4	7.5%	9%	22.5%	22.5%
5 - 10	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1574	3037	4146	4969	5465	7929
35	2138	4161	5839	6669	7753	10735
50	2890	5435	7893	9290	10519	14700
70	4059	8074	11525	13341	15184	23125
95	5394		15980	18299	21093	
120	6788		19594	24066	26281	
150	8444		24919	29113	33383	
185	10382		31676	37061	42310	
240	13338		41146	47837	54581	
300	16630		51858	59973	69405	
400	21738		66607	75800	92786	
500	27481					
630	34624					
800	43940					
1000	54808					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1429	2820	3920	4671	5134	
35	1977	3907	5463	6289	7356	
50	2706	5357	7426	8894	9833	
70	3853	7640	10938	12830	14529	
95	5254		15650	18214	20374	
120	6622		18321	23291	26085	
150	8275		24532	28336	32606	
185	10156		30276	35400	40369	
240	13120					
300	16366					
400	21504					
500	27172					
630	34158					
800	43473					
1000	54343					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1845				
50		2205				
70	2479	2686				
95	2799	3047	4119	4204	5569	
120	3388	3680	4629	4723	6278	
150	3978	4310	5308	5416	6749	7302
185	4562	4914	5991	6114	7534	8121
240	5562	5954	7074	7218	8898	9419
300	6649	7042	8293	8464	10045	11056
400	8432	8812	10060	10264	12176	12802

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2039	2138	2240	2352	2537	2670	2596	2733	3339	3519	3824	4029
300	2336	2465	2568	2712	2889	3043	2956	3114	3948	4159	4248	4476
400	2840	2992	3080	3244	3431	3608	3507	3688	4530	4758	4793	5042
500	3623	3817	3755	3948	4310	4533	4310	4533	5337	5620	5562	5861
630	4377	4611	4496	4731	5093	5353	5093	5353	6207	6530	6463	6797
800	5440	5721	5516	5964	6101	6422	6101	6422	7346	7728	7665	8059
1000	6436	6774	7067	7444	7561	7952	7561	7952	8987	9421	9660	10166

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 240	1596
1 Core x 300	1924
1 Core x 400	2424
1 Core x 630	3771

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 25	863
3 Core x 35	979
3 Core x 50	1244
3 Core x 70	1514
3 Core x 95	1777
3 Core x 120	2326
3 Core x 150	2875
3 Core x 185	3385
3 Core x 240	4275
3 Core x 300	5237
3 Core x 400	6540

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	154	0.75	180	1	200	1.5	238	2.5	327
CORE	3	0.5	184	0.75	223	1	251	1.5	311	2.5	432
CORE	4	0.5	207	0.75	248	1	292	1.5	363	2.5	523
CORE	5	0.5	230	0.75	288	1	338	1.5	432	2.5	627
CORE	6	0.5	261	0.75	327	1	392	1.5	501	2.5	755
CORE	7	0.5	282	0.75	360	1	436	1.5	567	2.5	849
CORE	8	0.5	316	0.75	403	1	486	1.5	639	2.5	956
CORE	10	0.5	366	0.75	480	1	589	1.5	777	2.5	1183
CORE	12	0.5	412	0.75	545	1	666	1.5	895	2.5	1335
CORE	14	0.5	474	0.75	609	1	763	1.5	1052	2.5	1578
CORE	16	0.5	521	0.75	687	1	855	1.5	1164	2.5	1779
CORE	19	0.5	585	0.75	776	1	985	1.5	1331	2.5	2090
CORE	24	0.5	708	0.75	977	1	1196	1.5	1647	2.5	2623
PAIR	1	0.5	154	0.75	180	1	200	1.5	238	2.5	327
PAIR	2	0.5	225	0.75	270	1	311	1.5	386	2.5	553
PAIR	3	0.5	270	0.75	338	1	403	1.5	515	2.5	764
PAIR	4	0.5	322	0.75	411	1	496	1.5	647	2.5	971
PAIR	5	0.5	377	0.75	487	1	596	1.5	790	2.5	1201
PAIR	6	0.5	435	0.75	567	1	690	1.5	921	2.5	1401
PAIR	7	0.5	477	0.75	622	1	775	1.5	1064	2.5	1598
PAIR	8	0.5	534	0.75	710	1	876	1.5	1179	2.5	1809
PAIR	10	0.5	639	0.75	843	1	1057	1.5	1439	2.5	2207
PAIR	12	0.5	726	0.75	985	1	1244	1.5	1684	2.5	2630
PAIR	14	0.5	797	0.75	1105	1	1395	1.5	1946	2.5	2997
PAIR	16	0.5	909	0.75	1217	1	1577	1.5	2174	2.5	3402
PAIR	19	0.5	1034	0.75	1440	1	1836	1.5	2541	2.5	3988
PAIR	24	0.5	1292	0.75	1808	1	2287	1.5	3193	2.5	5013
TRIAD	1	0.5	187	0.75	225	1	253	1.5	315	2.5	435
TRIAD	2	0.5	311	0.75	385	1	427	1.5	551	2.5	797
TRIAD	3	0.5	385	0.75	485	1	553	1.5	727	2.5	1074
TRIAD	4	0.5	463	0.75	595	1	692	1.5	912	2.5	1356
TRIAD	5	0.5	536	0.75	712	1	828	1.5	1118	2.5	1664
TRIAD	6	0.5	618	0.75	823	1	972	1.5	1290	2.5	1955
TRIAD	7	0.5	684	0.75	912	1	1085	1.5	1454	2.5	2228
TRIAD	8	0.5	770	0.75	1003	1	1214	1.5	1649	2.5	2541
TRIAD	10	0.5	911	0.75	1244	1	1476	1.5	2031	2.5	3133
TRIAD	12	0.5	1037	0.75	1429	1	1729	1.5	2371	2.5	3708
TRIAD	14	0.5	1179	0.75	1633	1	1977	1.5	2726	2.5	4269
TRIAD	16	0.5	1307	0.75	1820	1	2223	1.5	3088	2.5	4841
TRIAD	19	0.5	1508	0.75	2115	1	2588	1.5	3607	2.5	5676
TRIAD	24	0.5	1867	0.75	2647	1	3234	1.5	4542	2.5	7142
QUAD	1	0.5	214	0.75	261	1	301	1.5	375	2.5	537

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	307	0.75	344	1	390	1.5	475	2.5	656
PAIR	3	0.5	393	0.75	439	1	517	1.5	634	2.5	894
PAIR	4	0.5	471	0.75	540	1	628	1.5	795	2.5	1101
PAIR	5	0.5	555	0.75	638	1	757	1.5	931	2.5	1344
PAIR	6	0.5	613	0.75	741	1	851	1.5	1092	2.5	1566
PAIR	7	0.5	701	0.75	820	1	978	1.5	1235	2.5	1781
PAIR	8	0.5	797	0.75	906	1	1094	1.5	1400	2.5	2031
PAIR	10	0.5	940	0.75	1107	1	1332	1.5	1712	2.5	2492
PAIR	12	0.5	1050	0.75	1287	1	1538	1.5	2018	2.5	2851
PAIR	14	0.5	1216	0.75	1448	1	1766	1.5	2281	2.5	3373
PAIR	16	0.5	1369	0.75	1629	1	1980	1.5	2571	2.5	3816
PAIR	19	0.5	1563	0.75	1874	1	2290	1.5	3003	2.5	4461
PAIR	24	0.5	1945	0.75	2354	1	2878	1.5	3788	2.5	5612
TRIAD	2	0.5	379	0.75	436	1	494	1.5	613	2.5	847
TRIAD	3	0.5	471	0.75	555	1	644	1.5	816	2.5	1155
TRIAD	4	0.5	575	0.75	690	1	799	1.5	1003	2.5	1467
TRIAD	5	0.5	681	0.75	823	1	967	1.5	1234	2.5	1819
TRIAD	6	0.5	788	0.75	940	1	1110	1.5	1445	2.5	2135
TRIAD	7	0.5	870	0.75	1049	1	1245	1.5	1636	2.5	2427
TRIAD	8	0.5	973	0.75	1206	1	1415	1.5	1867	2.5	2768
TRIAD	10	0.5	1171	0.75	1458	1	1733	1.5	2291	2.5	3440
TRIAD	12	0.5	1356	0.75	1692	1	2023	1.5	2676	2.5	4032
TRIAD	14	0.5	1524	0.75	1924	1	2324	1.5	3089	2.5	4646
TRIAD	16	0.5	1715	0.75	2169	1	2609	1.5	3493	2.5	5272
TRIAD	19	0.5	1987	0.75	2521	1	3062	1.5	4108	2.5	6176
TRIAD	24	0.5	2492	0.75	3172	1	3859	1.5	5132	2.5	7818

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						737	1070	1483	2109
2 Core	195	299	419	629	1064	1630	2460	3338	4751
3 Core	259	417	594	892	1515	2316	3459	4732	6740
4 Core	337	541	777	1182	1994	3033	4535	6225	8934
5 Core	409	706	1044						
6 Core	492	771							
7 Core	538	866							
8 Core	623	1056							
10 Core	823	1304							
12 Core	987	1538							
14 Core	1122	1777							
16 Core	1300	2023							
19 Core	1515	2365							
24 Core	1933	3011							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	2964	3888	4929	6134	7476	9876	12368	16240	
3 Core	9498	12453	15785	19646	23942	31498	39505	51681	
4 Core	12451	16318	20820	25916	31602	41565	52074	68341	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	137	214				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	198	317	462	994	2110	3875

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMOURED, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMOURED CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	158	301	478			

Page 12 of 18

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	191
	22 AWG	0.32	210
	20 AWG	0.50	233
	18 AWG	0.80	275
	17 AWG	1.00	296
2 Pair	24 AWG	0.205	275
	22 AWG	0.32	309
	20 AWG	0.50	349
	18 AWG	0.80	428
	17 AWG	1.00	467

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	117
	22 AWG	0.32	132
	20 AWG	0.50	151
	18 AWG	0.80	187
	17 AWG	1.00	203
2 Pair	24 AWG	0.205	174
	22 AWG	0.32	210
	20 AWG	0.50	242
	18 AWG	0.80	312
	17 AWG	1.00	352

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	210
	22 AWG	0.32	230
	20 AWG	0.50	257
	18 AWG	0.80	302
	17 AWG	1.00	326
2 Pair	24 AWG	0.205	302
	22 AWG	0.32	336
	20 AWG	0.50	383
	18 AWG	0.80	469
	17 AWG	1.00	515

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	128
	22 AWG	0.32	145
	20 AWG	0.50	166
	18 AWG	0.80	204
	17 AWG	1.00	227
2 Pair	24 AWG	0.205	195
	22 AWG	0.32	230
	20 AWG	0.50	267
	18 AWG	0.80	342
	17 AWG	1.00	385

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	426	529		645
2.5	529	678		836
4	622	816		1021
6	808	1079		1365
10	1142	1561		1994
16	1513	2112		2778
25	2158	3107	3741	4082
35	2870	4161	4810	5492
50	3780	5527	6482	7319
70	5256	7721	9032	10226
95	6907	10171	11878	13481
120	8595	12709	15142	16874
150	10524	15584	18007	20679
185	13002	19272	22562	25567
240	16532	24554	28696	32607
300	20480	30424	35507	40442
400	26659	39660	45964	52719

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	474	583		706
2.5	583	734		899
4	679	874		1086
6	864	1143		1435
10	1207	1630		2073
16	1577	2179		2868
25	2238	3195	3840	4185
35	2957	4261	4918	5608
50	3878	5635	6602	7455
70	5375	7860	9185	10389
95	7047	10320	12045	13661
120	8741	12874	15342	17091
150	10698	15787	18233	20932
185	13197	19514	22831	25863
240	16766	24844	29021	32964
300	20757	30763	35886	40870
400	27007	40093	46451	53252

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	493	611		739
2.5	605	763		935
4	700	902		1127
6	887	1178		1482
10	1234	1671		2129
16	1608	2230		2930
25	2289	3273	3932	4286
35	3015	4345	5020	5723
50	3953	5749	6737	7603
70	5473	8008	9360	10586
95	7151	10480	12243	13873
120	8870	13070	15585	17353
150	10865	16040	18533	21271
185	13415	19837	23207	26291
240	17024	25235	29479	33484
300	21061	31220	36429	41482
400	27388	40662	47133	54016

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Strip Armoured/FRLS Sheathed FS Aluminium Power Cables

Sq.mm.	3 Core	4 Core
16	864	1117
25	1164	1481
35	1409	1819
50	1743	2258
70	2380	3100
95	2975	3872
120	3555	4659
150	4230	5542
185	5127	6696
240	6380	8344
300	7681	10079
400	9556	12518