

POLYCAB

IDEAS. CONNECTED.

POLYCAB INDIA LIMITED**PCC LP No. 04/2025-26 Dtd : 13th January 2026****List of Products Covered in Our PCC LP****Aluminium Armoured / Unarmoured Cables****Copper Armoured / Unarmoured Cables****HT Cables****1.9 KV / 3.3 KV Cables for Solar****Instrumentation Cables****Rubber Cables****JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables****RS 485 Cables****Fire Survival Cables****FS Aluminium Cables**

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		229	256		285
4		260	280		326
6		316	345		413
10		400	446		567
16	257	455	479		606
25	339	486	639	742	793
35	411	606	812	901	1028
50	505	785	1056	1221	1373
70	646	1051	1447	1646	1865
95	775	1298	1782	2064	2325
120	907	1564	2258	2610	2949
150	1081	1923	2771	3093	3626
185	1329	2311	3430	3915	4460
240	1642	3065	4381	4918	5759
300	2021	3756	5414	6050	7098
400	2552	4878	6920	7728	8861
500	3180	6587	9276	10924	12250
630	3923	8102	11792	13386	16080
800	4822				
1000	5931				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Armoured			
	Power (Al.)			
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
	Power Single Core (Al.)			
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		150	187		224
6		209	248		301
10		301	338		396
16	146	307	380		504
25	211	396	557	706	743
35	274	519	737	799	886
50	350	652	908	1081	1184
70	483	938	1308	1477	1700
95	622	1113	1591	1889	2026
120	782	1401	2158	2452	2609
150	967	1741	2540	2868	3230
185	1197	2077	3201	3670	3999
240	1519	2717	4132	4490	5224
300	1877	3321	5064	5820	6361
400	2417	4143	6320	7271	8131
500	3036	5286	8943	10033	11341
630	3762	6728	11220	13311	15177
800	4695				
1000	5919				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		627	839	1076	1577	1987	2189
6		882	1212	1583	2294	2802	3215
10		1403	1971	2573	3489		
16	1197	2078	2881	3804	5000		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	312	441	14	1447	2274
3	397	570	16	1617	2583
4	491	735	19	1918	3040
5	596	902	24	2399	3807
6	710	1062	27	2669	4269
7	781	1198	30	2977	5135
8	999	1462	37	3861	5998
10	1137	1683	44	4510	7005
12	1264	1956	61	6639	10155

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
2 to 4 Core	7.5%	9%	22.5%	22.5%
5 to 10 Core	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		534	761	941
6		780	1123	1383
10		1352	1904	2268
16	1001	1904	2765	3549

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	244	369	14	1198	2165
3	344	515	16	1434	2481
4	441	694	19	1716	2934
5	538	869	24	2175	3704
6	647	1031	27	2401	4114
7	733	1175	30	2850	4877
8	892	1332	37	3692	5849
10	1065	1526	44	4318	6972
12	1137	1868	61	6317	9595

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D OXYGEN INDEX (FR)	4%
E) HR PVC Insulation	17.5%
HR PVC I/S & O/S	7.5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
G) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Unarmd			
2 - 4	7.5%	9%	22.5%	22.5%
5 - 10	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1731	3341	4561	5466	6012	8722
35	2352	4577	6423	7336	8528	11809
50	3179	5979	8682	10219	11571	16170
70	4465	8881	12678	14675	16702	25438
95	5933		17578	20129	23202	
120	7467		21553	26473	28909	
150	9288		27411	32024	36721	
185	11420		34844	40767	46541	
240	14672		45261	52621	60039	
300	18293		57044	65970	76346	
400	23912		73268	83380	102065	
500	30229					
630	38086					
800	48334					
1000	60289					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1572	3102	4312	5138	5647	
35	2175	4298	6009	6918	8092	
50	2977	5893	8169	9783	10816	
70	4238	8404	12032	14113	15982	
95	5779		17215	20035	22411	
120	7284		20153	25620	28694	
150	9103		26985	31170	35867	
185	11172		33304	38940	44406	
240	14432					
300	18003					
400	23654					
500	29889					
630	37574					
800	47820					
1000	59777					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1983				
50		2370				
70	2665	2887				
95	3009	3276	4428	4519	5987	
120	3642	3956	4976	5077	6749	
150	4276	4633	5706	5822	7255	7850
185	4904	5283	6440	6573	8099	8730
240	5979	6401	7605	7759	9565	10125
300	7148	7570	8915	9099	10798	11885
400	9064	9473	10815	11034	13089	13762

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%
2) Pressure Extruded PVC Innersheath	19.5%
3) Round Wire Armouring - Up to 11 KV (E)	30%
11 KV (UE) & Above	33%
4) FRLS PVC Inner Sheath	7.5%
5) FRLS PVC Outer Sheath	7.5%
6) FR Sheath with Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable confirming to IS 7098 / (PART-II) 1985 with latest amendments.

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2192	2352	2408	2587	2727	2937	2791	3006	3589	3871	4111	4432
300	2511	2712	2761	2983	3106	3347	3178	3425	4244	4575	4567	4924
400	3053	3291	3311	3568	3688	3969	3770	4057	4870	5234	5152	5546
500	3895	4199	4037	4343	4633	4986	4633	4986	5737	6182	5979	6447
630	4705	5072	4833	5204	5475	5888	5475	5888	6673	7183	6948	7477
800	5848	6293	5930	6560	6559	7064	6559	7064	7897	8501	8240	8865
1000	6919	7451	7597	8188	8128	8747	8128	8747	9661	10363	10385	11183

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 240	1716
1 Core x 300	2068
1 Core x 400	2606
1 Core x 630	4054

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 25	992
3 Core x 35	1126
3 Core x 50	1431
3 Core x 70	1741
3 Core x 95	1910
3 Core x 120	2500
3 Core x 150	3091
3 Core x 185	3639
3 Core x 240	4596
3 Core x 300	5630
3 Core x 400	7031

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	162	0.75	189	1	210	1.5	250	2.5	343
CORE	3	0.5	193	0.75	234	1	264	1.5	327	2.5	454
CORE	4	0.5	217	0.75	260	1	307	1.5	381	2.5	549
CORE	5	0.5	242	0.75	302	1	355	1.5	454	2.5	658
CORE	6	0.5	274	0.75	343	1	412	1.5	526	2.5	793
CORE	7	0.5	296	0.75	378	1	458	1.5	595	2.5	891
CORE	8	0.5	332	0.75	423	1	510	1.5	671	2.5	1004
CORE	10	0.5	384	0.75	504	1	618	1.5	816	2.5	1242
CORE	12	0.5	433	0.75	572	1	699	1.5	940	2.5	1402
CORE	14	0.5	498	0.75	639	1	801	1.5	1105	2.5	1657
CORE	16	0.5	547	0.75	721	1	898	1.5	1222	2.5	1868
CORE	19	0.5	614	0.75	815	1	1034	1.5	1398	2.5	2195
CORE	24	0.5	743	0.75	1026	1	1256	1.5	1729	2.5	2754
PAIR	1	0.5	162	0.75	189	1	210	1.5	250	2.5	343
PAIR	2	0.5	236	0.75	284	1	327	1.5	405	2.5	581
PAIR	3	0.5	284	0.75	355	1	423	1.5	541	2.5	802
PAIR	4	0.5	338	0.75	432	1	521	1.5	679	2.5	1020
PAIR	5	0.5	396	0.75	511	1	626	1.5	830	2.5	1261
PAIR	6	0.5	457	0.75	595	1	725	1.5	967	2.5	1471
PAIR	7	0.5	501	0.75	653	1	814	1.5	1117	2.5	1678
PAIR	8	0.5	561	0.75	746	1	920	1.5	1238	2.5	1899
PAIR	10	0.5	671	0.75	885	1	1110	1.5	1511	2.5	2317
PAIR	12	0.5	762	0.75	1034	1	1306	1.5	1768	2.5	2762
PAIR	14	0.5	837	0.75	1160	1	1465	1.5	2043	2.5	3147
PAIR	16	0.5	954	0.75	1278	1	1656	1.5	2283	2.5	3572
PAIR	19	0.5	1086	0.75	1512	1	1928	1.5	2668	2.5	4187
PAIR	24	0.5	1357	0.75	1898	1	2401	1.5	3353	2.5	5264
TRIAD	1	0.5	196	0.75	236	1	266	1.5	331	2.5	457
TRIAD	2	0.5	327	0.75	404	1	448	1.5	579	2.5	837
TRIAD	3	0.5	404	0.75	509	1	581	1.5	763	2.5	1128
TRIAD	4	0.5	486	0.75	625	1	727	1.5	958	2.5	1424
TRIAD	5	0.5	563	0.75	748	1	869	1.5	1174	2.5	1747
TRIAD	6	0.5	649	0.75	864	1	1021	1.5	1355	2.5	2053
TRIAD	7	0.5	718	0.75	958	1	1139	1.5	1527	2.5	2339
TRIAD	8	0.5	809	0.75	1053	1	1275	1.5	1731	2.5	2668
TRIAD	10	0.5	957	0.75	1306	1	1550	1.5	2133	2.5	3290
TRIAD	12	0.5	1089	0.75	1500	1	1815	1.5	2490	2.5	3893
TRIAD	14	0.5	1238	0.75	1715	1	2076	1.5	2862	2.5	4482
TRIAD	16	0.5	1372	0.75	1911	1	2334	1.5	3242	2.5	5083
TRIAD	19	0.5	1583	0.75	2221	1	2717	1.5	3787	2.5	5960
TRIAD	24	0.5	1960	0.75	2779	1	3396	1.5	4769	2.5	7499
QUAD	1	0.5	225	0.75	274	1	316	1.5	394	2.5	564

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	322	0.75	361	1	410	1.5	499	2.5	689
PAIR	3	0.5	413	0.75	461	1	543	1.5	666	2.5	939
PAIR	4	0.5	495	0.75	567	1	659	1.5	835	2.5	1156
PAIR	5	0.5	583	0.75	670	1	795	1.5	978	2.5	1411
PAIR	6	0.5	644	0.75	778	1	894	1.5	1147	2.5	1644
PAIR	7	0.5	736	0.75	861	1	1027	1.5	1297	2.5	1870
PAIR	8	0.5	837	0.75	951	1	1149	1.5	1470	2.5	2133
PAIR	10	0.5	987	0.75	1162	1	1399	1.5	1798	2.5	2617
PAIR	12	0.5	1103	0.75	1351	1	1615	1.5	2119	2.5	2994
PAIR	14	0.5	1277	0.75	1520	1	1854	1.5	2395	2.5	3542
PAIR	16	0.5	1437	0.75	1710	1	2079	1.5	2700	2.5	4007
PAIR	19	0.5	1641	0.75	1968	1	2405	1.5	3153	2.5	4684
PAIR	24	0.5	2042	0.75	2472	1	3022	1.5	3977	2.5	5893
TRIAD	2	0.5	398	0.75	458	1	519	1.5	644	2.5	889
TRIAD	3	0.5	495	0.75	583	1	676	1.5	857	2.5	1213
TRIAD	4	0.5	604	0.75	725	1	839	1.5	1053	2.5	1540
TRIAD	5	0.5	715	0.75	864	1	1015	1.5	1296	2.5	1910
TRIAD	6	0.5	827	0.75	987	1	1166	1.5	1517	2.5	2242
TRIAD	7	0.5	914	0.75	1101	1	1307	1.5	1718	2.5	2548
TRIAD	8	0.5	1022	0.75	1266	1	1486	1.5	1960	2.5	2906
TRIAD	10	0.5	1230	0.75	1531	1	1820	1.5	2406	2.5	3612
TRIAD	12	0.5	1424	0.75	1777	1	2124	1.5	2810	2.5	4234
TRIAD	14	0.5	1600	0.75	2020	1	2440	1.5	3243	2.5	4878
TRIAD	16	0.5	1801	0.75	2277	1	2739	1.5	3668	2.5	5536
TRIAD	19	0.5	2086	0.75	2647	1	3215	1.5	4313	2.5	6485
TRIAD	24	0.5	2617	0.75	3331	1	4052	1.5	5389	2.5	8209

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						792	1150	1594	2267
2 Core	210	321	450	676	1144	1752	2645	3588	5107
3 Core	278	448	639	959	1629	2490	3718	5087	7246
4 Core	362	582	835	1271	2144	3260	4875	6692	9604
5 Core	440	759	1122						
6 Core	529	829							
7 Core	578	931							
8 Core	670	1135							
10 Core	885	1402							
12 Core	1061	1653							
14 Core	1206	1910							
16 Core	1398	2175							
19 Core	1629	2542							
24 Core	2078	3237							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	3186	4180	5299	6594	8037	10617	13296	17458	
3 Core	10210	13387	16969	21119	25738	33860	42468	55557	
4 Core	13385	17542	22382	27860	33972	44682	55980	73467	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	144	225				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	208	333	485	1044	2216	4069

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMOURED, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMOURED CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	166	316	502			

Page 12 of 18

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	205
	22 AWG	0.32	226
	20 AWG	0.50	250
	18 AWG	0.80	296
	17 AWG	1.00	318
2 Pair	24 AWG	0.205	296
	22 AWG	0.32	332
	20 AWG	0.50	375
	18 AWG	0.80	460
	17 AWG	1.00	502

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	126
	22 AWG	0.32	142
	20 AWG	0.50	162
	18 AWG	0.80	201
	17 AWG	1.00	218
2 Pair	24 AWG	0.205	187
	22 AWG	0.32	226
	20 AWG	0.50	260
	18 AWG	0.80	335
	17 AWG	1.00	378

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	226
	22 AWG	0.32	247
	20 AWG	0.50	276
	18 AWG	0.80	325
	17 AWG	1.00	350
2 Pair	24 AWG	0.205	325
	22 AWG	0.32	361
	20 AWG	0.50	412
	18 AWG	0.80	504
	17 AWG	1.00	554

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	138
	22 AWG	0.32	156
	20 AWG	0.50	178
	18 AWG	0.80	219
	17 AWG	1.00	244
2 Pair	24 AWG	0.205	210
	22 AWG	0.32	247
	20 AWG	0.50	287
	18 AWG	0.80	368
	17 AWG	1.00	414

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	458	569		693
2.5	569	729		899
4	669	877		1098
6	869	1160		1467
10	1228	1678		2144
16	1626	2270		2986
25	2320	3340	4022	4388
35	3085	4473	5171	5904
50	4064	5942	6968	7868
70	5650	8300	9709	10993
95	7425	10934	12769	14492
120	9240	13662	16278	18140
150	11313	16753	19358	22230
185	13977	20717	24254	27485
240	17772	26396	30848	35053
300	22016	32706	38170	43475
400	28658	42635	49411	56673

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	510	627		759
2.5	627	789		966
4	730	940		1167
6	929	1229		1543
10	1298	1752		2228
16	1695	2342		3083
25	2406	3435	4128	4499
35	3179	4581	5287	6029
50	4169	6058	7097	8014
70	5778	8450	9874	11168
95	7576	11094	12948	14686
120	9397	13840	16493	18373
150	11500	16971	19600	22502
185	14187	20978	24543	27803
240	18023	26707	31198	35436
300	22314	33070	38577	43935
400	29033	43100	49935	57246

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outsheathed Fire Survival Cables

Rate/Mtr.

Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	530	657		794
2.5	650	820		1005
4	753	970		1212
6	954	1266		1593
10	1327	1796		2289
16	1729	2397		3150
25	2461	3518	4227	4607
35	3241	4671	5397	6152
50	4249	6180	7242	8173
70	5883	8609	10062	11380
95	7687	11266	13161	14913
120	9535	14050	16754	18654
150	11680	17243	19923	22866
185	14421	21325	24948	28263
240	18301	27128	31690	35995
300	22641	33562	39161	44593
400	29442	43712	50668	58067

Page 17 of 18

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Strip Armoured/FRLS Sheathed FS Aluminium Power Cables

Sq.mm.	3 Core	4 Core
16	929	1201
25	1251	1592
35	1515	1955
50	1874	2427
70	2559	3333
95	3198	4162
120	3822	5008
150	4547	5958
185	5512	7198
240	6859	8970
300	8257	10835
400	10273	13457